

# PULVERIZER

The Pulverizer has long been one of the farmer's most valuable tools. When pulled behind a disc or field cultivator, the Pulverizer will help create an ideal seedbed with fewer trips across the field. Good yields start with a properly prepared seedbed. A firm seedbed is critical to maintain a uniform planting depth. The seedbed should be firm with fine soil particles at the seed depth and should have a layer of loose mulch on the surface to retard evaporation and conserve moisture. Some of the most valuable soil nutrients are locked in the clods left in the field. The Brillion Pulverizer crushes clods to release those nutrients for use by growing plants. At the same time air pockets are eliminated and moisture is drawn up the root zone by capillary action. Good seed to soil contact creates more uniform germination, pollination and maturity...and that means increased crop yield and greater profits.

## *Brillion Pulverizers...Since 1985*

### PP/P SERIES – 5' TO 8' MODELS



Model PPD-5

- Working Width: 5' to 8'
- Three-Point Hitch Models or Pull-Type Models Without Transport Tires
- Cat. I Three-Point Hitch on 5' to 7' Models
- Cat. I, II Three-Point Hitch on 8' Models
- Pulverizer Wheel Styles:
  - 16" Notched Gray Iron
  - 20" Notched Ductile Iron
  - 16" Crowfoot Gray Iron

### PP/P SERIES – 10' TO 20' MODELS



Model PPD-16

- Working Width: 10' to 20'
- Three-Point Hitch Models or Pull-Type Models Without Transport Tires
- Pulverizer Wheel Styles for Three-Point Hitch Models:
  - 20" Notched Ductile Iron
  - 20" Optimizer® Ductile Iron
- Cat. I, II Three-Point Hitch
- Pulverizer Wheel Styles for Pull-Type Models:
  - 20" Notched Ductile Iron
  - 20" Notched Gray Iron
  - 20" Crowfoot Ductile Iron

### SD SERIES



Model SD-12

- Double Roller Configuration – Same Foundation as on Brillion Sure Stand Seeders
- 6', 8', 10' or 12' Three-Point Hitch Models Available
- Cat. I Three-Point Hitch on 6' Model
- Cat. I, II Three-Point Hitch on 8', 10' and 12' Models
- Pull-Type Models Available in 8', 10' or 12' Sizes
- Gray Iron Pulverizer Wheels with Larger Diameter Wheels on the Front Roller

### PFT SERIES



Model PFT18B12

- Floating Ring Design Best Suited for Use with Companion Primary Tillage Tool
- Cat. II, III Three-Point Hitch Models Available in Sizes from 6' to 18'
- Pull-Type Models Available in Sizes from 10' to 18'
- 20" Ductile Iron Rings with 14" Inside Diameter



## PT SERIES



Model PDT-14

- Rotating Frame Transport Models
- Working Width: 10' to 20'
- Pulverizer Wheel Styles:
  - 20" Notched Ductile Iron
  - 20" Notched Gray Iron
  - 20" Crowfoot Ductile Iron
  - 20" Optimizer<sup>®</sup> Ductile Iron

## X SERIES



Model XO108W72

- Working Width: 19' to 27'
- Transport Heights Under 7'10"; Transport Width 10'11"
- Pulverizer Axle Size: 4 1/2"
- Pulverizer Wheel Styles:
  - 20" Notched Ductile Iron
  - 20" Optimizer Ductile Iron
  - 20" Crowfoot Gray Iron
  - 20" Notched Gray Iron

## XL SERIES



Model XLO144W120

- Working Width: 28' to 36'
- Transport Heights Under 8'; Transport Width 13'4"
- Telescoping Drawbar
- Pulverizer Axle Size: 4 1/2"
- Pulverizer Wheel Styles:
  - 20" Notched Ductile Iron
  - 20" Optimizer Ductile Iron
  - 20" Crowfoot Gray Iron
  - 20" Notched Gray Iron

## XXL SERIES



Model XXL184W184

- Working Width: 38' to 46'
- Transport Heights Under 8'9"; Transport Width 16'9"
- Telescoping Drawbar
- Pulverizer Axle Size: 4"
- Pulverizer Wheel Styles:
  - 20" Notched Ductile Iron
  - 20" Optimizer Ductile Iron
  - 20" Crowfoot Ductile Iron

## WFP SERIES – 22' TO 36' MODELS



Model WFPDS36

- Patented Wing Float Design
- Working Width: 23'4" to 37'4"
- Transport Heights Under 11'; Transport Width 14'
- Telescoping Drawbar on 28' to 36' Models
- Pulverizer Axle Size: 8"
- Pulverizer Wheel Styles:
  - 20" Notched Ductile Iron
  - 20" Optimizer Ductile Iron

## WFP SERIES – 38' TO 46' MODELS


















*New!*

- Patented Wing Float Design
- Working Width: 38' to 46'
- Transport Heights Under 9'; Transport Width 17'5"
- Telescoping Drawbar
- Pulverizer Axle Size: 8"
- Pulverizer Wheel Styles:
  - 20" Notched Ductile Iron
  - 20" Optimizer Ductile Iron



# PULVERIZER WHEEL USAGE GUIDE

Also available from  
**Brillion Farm Equipment**

	Notched Wheel	Optimizer® Wheel	Crowfoot Wheel
Firms and Levels Seedbed for Enhanced Planter/Drill Performance			
Pins Residue to Soil Surface			
Pushes Stones Into Soil			
Eliminates Soil Crusting			
Breaks Root Balls & Clods			
Texturizes the Soil Surface for Improved Water Intake			
Post-Plant Firming of Seedbed for Improved Seed to Soil Contact			
Firms and Levels Sandy/Coarse Textured Soils			

Pulverizer wheels are not designed to operate in excessively wet conditions. Scrapers (available for notched wheels) are recommended when Pulverizers are used as companion implements during tillage and seedbed preparations. Gray iron wheels are covered by a standard 1-year warranty, while ductile iron wheels are covered by a 5-year limited warranty.



For detailed product specifications, visit [www.brillionfarmeq.com](http://www.brillionfarmeq.com)



Pulvi-Mulchers



Agricultural & Landscape Seeders



Food Plot Seeders



Till 'N Seed®



220 N. Francis Street  
P.O. Box 8  
Brillion, WI 54110  
Phone: 920.524.2220  
Toll Free: 855.320.0373  
Fax: 888.761.8568

