

Brilliant™

Farm Equipment

A LANDOLL PRODUCT

DOUBLE SEEDER HITCH



- Pull Any Combination of Two 8', 10' or 12' Seeders or Drills
- Hydraulically Actuated from Transport to Field
- All Plumbing and Electrical Wiring Included
- Center Line Driving Available
- Transport Width as Wide as Widest Machine



Brilliant™
Farm Equipment

www.brilliantfarmeq.com

PULL DOUBLE. WORK HALF.



The unique design of the Double Seeder Hitch allows for pulling any combination of 8', 10', or 12' pull-type seeders in tandem to expand the seeding width up to a maximum of 24 feet. The over-the-top design maintains a transport width only as wide as the widest seeder. The center flex pivot and wide range of adjustments lets each seeder follow the soil's natural contours for consistent seeder operation. The Double Seeder Hitch incorporates low profile flotation tires on the front frame and a caster wheel and tire on the rear frame to keep wheel tracks in the field to a minimum. The rear tongue utilizes an adjustable hitch plate for easy hook-ups. The Double Seeder Hitch has all the features to save time when planting, while still being a cost effective addition to your seeder line-up.

SPECIFICATIONS

	BDH-512
Approximate Weight	2,200 lbs. (998 kg)
Working Width	Dependent on Implements Used
Transport Width (Less Implements)	8 ft. 5 in. (2.57 m)
Transport Height	7 ft. 9 in. (2.36 m)
Overall Length (Less Implements)	28 ft. 7 in. (8.58 m)
Frame Structure	4 in. x 6 in. x .188 in. (102 x 152 x 4.78 mm) 4 in. x 7 in. x .188 in. (102 x 178 x 4.78 mm)
Tire Size (Front)	27 x 9.50-15 10 ply NHS
Tire Size (Rear Caster)	20.5 x 8
Hydraulic Circuits Required	3
Sizes of Implements Used	Any Combination of 8 ft., 10 ft., 12 ft.
Safety Chain	Standard
Rear Implement Wiring	Standard
Horsepower Requirements	Adequate to Safely Support Implements
Recommended Operating Speed	3 to 6 MPH (5 to 10 km/h)

Specifications subject to change without notice.



Brillion Farm Equipment
 220 N. Francis Street
 P.O. Box 8
 Brillion, WI 54110
 Toll Free: 855.320.0373
 Fax: 888.761.8568