

Series 580 Flex-Wing Tandem Disc Harrow

Cutting Width	Bearing Hanger Type	Number of Discs	Approx. Weight	Number of Bearings	Transport Wheels	Wing Size	Approx. DB Hp
Narrow Frame – 22" Round Blades / Base Weight 8" Disc Spacing							
17' 5"	Rigid	52	7,458 lbs.	16	6	6F / 7R	100 HP
17' 5"	Flex	52	7,718 lbs.	16	6	6F / 7R	100 HP
19' 11"	Rigid	62	7,902 lbs.	24	6	8F / 10R	110 HP
19' 11"	Flex	62	8,282 lbs.	24	6	8F / 10R	110 HP
Narrow Frame – 22" Round Blades / Base Weight 9" Disc Spacing							
17' 11"	Rigid	48	7,352 lbs.	16	6	6F / 7R	100 HP
17' 11"	Flex	48	7,612 lbs.	16	6	6F / 7R	100 HP
20' 9"	Rigid	56	7,702 lbs.	24	6	8F / 9R	110 HP
20' 9"	Flex	56	8,082 lbs.	24	6	8F / 9R	110 HP
Narrow Frame – 22" Round Blades / Base Weight 9" FT / 8" RR Disc Spacing							
17' 5"	Rigid	52	7,406 lbs.	16	6	6F / 8R	100 HP
17' 5"	Flex	52	7,626 lbs.	16	6	6F / 8R	100 HP
21' 2"	Rigid	60	7,848 lbs.	24	6	8F / 10R	110 HP
21' 2"	Flex	60	8,228 lbs.	24	6	8F / 10R	110 HP
Wide Frame – 22" Round Blades / Base Weight 8" Disc Spacing							
22' 6"	Rigid	70	8,504 lbs.	24	8	10F / 11R	125 HP
22' 6"	Flex	70	8,884 lbs.	24	8	10F / 11R	125 HP
25' 0"	Rigid	76	8,884 lbs.	24	8	12F / 13R	140 HP
25' 0"	Flex	76	9,264 lbs.	24	8	12F / 13R	140 HP
Wide Frame – 22" Round Blades / Base Weight 9" Disc Spacing							
22' 2"	Rigid	60	8,292 lbs.	24	8	9F / 10R	125 HP
22' 2"	Flex	60	8,672 lbs.	24	8	9F / 10R	125 HP
25' 0"	Rigid	68	8,764 lbs.	24	8	11F / 12R	140 HP
25' 0"	Flex	68	9,144 lbs.	24	8	11F / 12R	140 HP
Wide Frame – 22" Round Blades / Base Weight 9" FT / 8" RR Disc Spacing							
22' 6"	Rigid	64	8,398 lbs.	24	8	9F / 11R	125 HP
22' 6"	Flex	64	8,778 lbs.	24	8	9F / 11R	125 HP
25' 0"	Rigid	72	8,708 lbs.	24	8	11F / 13R	140 HP
25' 0"	Flex	72	9,088 lbs.	24	8	11F / 13R	140 HP