	WL-3630-30	WLC-3630-30	WCL-3630-30	WCC-3630-30	WOL-3630-30	WOO-3630-30	WL-3630-36	WLC-3630-36	WCL-3630-36	WCC-3630-36	WOL-3630-36	WOO-3630-36
Approximate Weight	27,700 lbs. (12,565 kg)	26,984 lbs. (12,240 kg)	27,302 lbs. (12,384 kg)	26,586 lbs. (12,059 kg)	28,431 lbs. (12,896 kg)	28,843 lbs. (13,083 kg)	29,900 lbs. (13,562 kg)	29,059 lbs. (13,181 kg)	29,438 lbs. (13,353 kg)	28,597 lbs. (12,971 kg)	30,775 lbs. (13,959 kg)	31,271 lbs. (14,184 kg)
Working Width	30 ft. 0 in. (9.1 m)	36 ft. 6 in. (11.1 m)	36 ft. 6 in. (11.1 m)	36 ft. 6 in. (11.1 m)	36 ft. 6 in. (11,1 m)	36 ft. 6 in. (11.1 m)	36 ft. 6 in. (11.1 m)					
Transport Width	19 ft. 0 in. (5.8 m)											
Transport Height	12 ft. 10 in. (3.9 m)											
Overall Length (Transport)	26 ft. 0 in. (7.9 m)											
Road Clearance	15 in. (381 mm)											
Type of Pulverizer Wheel - Front	20 in. (500 mm) Notched Ductile Iron	20 in. (500 mm) Notched Ductile Iron	20 in. (500 mm) Crowfoot Ductile Iron	20 in. (500 mm) Crowfoot Ductile Iron	20 in. (500 mm) Optimizer Ductile Iron	20 in. (500 mm) Optimizer Ductile Iron	20 in. (500 mm) Notched Ductile Iron	20 in. (500 mm) Notched Ductile Iron	20 in. (500 mm) Crowfoot Ductile Iron	20 in. (500 mm) Crowfoot Ductile Iron	20 in. (500 mm) Optimizer Ductile Iron	20 in. (500 mm) Optimizer Ductile Iron
Number of Pulverizer Wheels - Front	96	96	63	63	63	63	114	114	75	75	75	75
Type of Pulverizer Wheel - Rear	20 in. (500 mm) Notched Ductile Iron	20 in. (500 mm) Crowfoot Ductile Iron	20 in. (500 mm) Notched Ductile Iron	20 in. (500 mm) Crowfoot Ductile Iron	20 in. (500 mm) Notched Ductile Iron	20 in. (500 mm) Optimizer Ductile Iron	20 in. (500 mm) Notched Ductile Iron	20 in. (500 mm) Crowfoot Ductile Iron	20 in. (500 mm) Notched Ductile Iron	20 in. (500 mm) Crowfoot Ductile Iron	20 in. (500 mm) Notched Ductile Iron	20 in. (500 mm) Optimizer Ductile Iron
Number of Pulverizer Wheels - Rear	96	63	96	63	96	63	114	75	114	75	114	75
Rear Roller Scrapers	Standard	N/A										
Roller Axle Size	8 in. (203 mm)											
Type of Shanks	Heavy-Duty Two-Piece S-Tine Shank 1.75 in. x 0.625 in. (44.5 x 15.9 mm)	Heavy-Duty Two-Piece S-Tine Shank 1.75 in. x 0.625 in. (44.5 x 15.9 mm)	Heavy-Duty Two-Piece S-Tine Shank 1.75 in. x 0.625 in. (44.5 x 15.9 mm)	Heavy-Duty Two-Piece S-Tine Shank 1.75 in. x 0.625 in. (44.5 x 15.9 mm)	Heavy-Duty Two-Piece S-Tine Shank 1.75 in. x 0.625 in. (44.5 x 15.9 mm)	Heavy-Duty Two-Piece S-Tine Shank 1.75 in. x 0.625 in. (44.5 x 15.9 mm)	Heavy-Duty Two-Piece S-Tine Shank 1.75 in. x 0.625 in. (44.5 x 15.9 mm)	Heavy-Duty Two-Piece S-Tine Shank 1.75 in. x 0.625 in. (44.5 x 15.9 mm)	Heavy-Duty Two-Piece S-Tine Shank 1.75 in. x 0.625 in. (44.5 x 15.9 mm)	Heavy-Duty Two-Piece S-Tine Shank 1.75 in. x 0.625 in. (44.5 x 15.9 mm)	Heavy-Duty Two-Piece S-Tine Shank 1.75 in. x 0.625 in. (44.5 x 15.9 mm)	Heavy-Duty Two-Piece S-Tine Shank 1.75 in. x 0.625 in. (44.5 x 15.9 mm)
Number of Shanks	63	63	63	63	63	63	75	75	75	75	75	75
Nominal Shank Spacing	6 in. (152 mm)											
Maximum Shank Depth of Operation	5 in. (127 mm)											
Under Frame Clearance	25 in. (635 mm)											
Hydraulically Actuated Spike Leveling Bar	Standard											
Hitch	Pull-Type with Hydraulic Lift											
Tire Size	(4) 380/55R x 16.5											
Hydraulic Circuits Required	3 (+1 for Rear Hitch)											
Rear Hitch	Optional											
Front Roller Scraper Kit	Optional	Optional	N/A	N/A	N/A	N/A	Optional	Optional	N/A	N/A	N/A	N/A
Land Leveler Kit	Optional											
V-Leveler Kit	Optional											
Independent Hydraulic Tooth Control	Standard											
LED Warning Lights & SMV Emblem	Standard											
Safety Chain Kit	Standard											
Powder Coat Paint	Standard											
Horsepower Requirements	10 to 12 HP (7.5 to 8.9 kW) per ft.	10 to 12 HP (7.5 to 8.9 kW) per ft.	10 to 12 HP (7.5 to 8.9 kW) per ft.	10 to 12 HP (7.5 to 8.9 kW) per ft.	10 to 12 HP (7.5 to 8.9 kW) per ft.	10 to 12 HP (7.5 to 8.9 kW) per ft.	10 to 12 HP (7.5 to 8.9 kW) per ft.	10 to 12 HP (7.5 to 8.9 kW) per ft.	10 to 12 HP (7.5 to 8.9 kW) per ft.	10 to 12 HP (7.5 to 8.9 kW) per ft.	10 to 12 HP (7.5 to 8.9 kW) per ft.	10 to 12 HP (7.5 to 8.9 kW) per ft.
Recommended Operating Speed	6 to 8 MPH (10 to 13 km/h)											