

Model		Speedrower® 160 PLUS	Speedrower® 220 PLUS	Speedrower® 260 PLUS
Engine		FPT 4-cylinder, Tier 4B	FPT 6-cylinder, Tier 4B	FPT 6-cylinder, Tier 4B
ECOBlue™ SCR HI-eSCR system (Selective Catalytic Reduction)		●	●	●
Displacement	cu. In. (L)	247 (4.5)	411 (6.7)	411 (6.7)
Aspiration		Turbocharged with air-to-air intercooler	Turbocharged with air-to-air intercooler	Turbocharged with air-to-air intercooler
Rated engine power ISO - ECE R120	hp (kW)	150 (112)	210 (156)	250 (186)
Max engine power ISO - ECE R120	hp (kW)	161 (120)	220 (164)	261 (194)
Fuel injection pump		Electronically controlled high-pressure common rail	Electronically controlled high-pressure common rail	Electronically controlled high-pressure common rail
Batteries / alternator		1, 12-volt 925 CCA / 150 amp	2, 12-volt 650 CCA / 150 amp	2, 12-volt 650 CCA / 150 amp
Fuel capacity	gal. (L)	120 (454)	120 (454)	120 (454)
DEF capacity	gal. (L)	19 (71.9)	19 (71.9)	19 (71.9)
Constant clean, rotating wand cooling system pre-cleaner		●	●	●
Transmission		SensiDrive™ Infinitely Variable Hydrostatic Ground Drive		
Operating modes		In-Field / Transport	In-Field / Transport	In-Field / Transport
Active hydrostatic system pressure monitoring & automatic compensation		●	●	●
Final drive		Double reduction planetary	Double reduction planetary	Double reduction planetary
Hydrostatic steering		Electronically controlled - Customizable resistance	Electronically controlled - Customizable resistance	Electronically controlled - Customizable resistance
Active rear axle steering		-	● High Speed Version	● High Speed Version
CommandGrip™ Controlled, customizable speeds		●	●	●
In-field speed range	mph (kph)	0-20 (0-32)	0-20 (0-32)	0-20 (0-32)
Transport speed range - Standard speed version	mph (kph)	0-22 (0-35.4)	0-22 (0-35.4)	0-22 (0-35.4)
Transport speed range - High-speed version	mph (kph)	-	0-30 (0-48.3)	0-30 (0-48.3)
Max gradeability rating* - Standard speed version		51%	70%	70%
Max gradeability rating* - High-speed version		-	46%	46%
Tires/Wheels				
18.4 x 26 12 PR R4 Industrial tread		○	○	○
21L x 2814 PR R4 Industrial tread		○	○	○
600/65 R28 R1W Deep cleat ag. tread**		○	○	○
580/70 R26 R3 Button turf tread**		○	○	○
Terraglide™ solid beam, air-ride rear axle		●	●	●
3° HD, fork caster with 14L x 16.1 rear tire & wheel		●	●	●
3° HD, cast single-arm caster with 16.5L x 16.1 rear tire & wheel**		-	○	○
Operator's Area				
Seat mounted, adjustable right hand console		●	●	●
Comfort Ride™ cab suspension system		●	●	●
Tinted front/rear cab glass		●	●	●
Instructor's seating		●	●	●
Standard cab package		○	○	○
Deluxe cab package		○	○	○
Premium cab package		○	○	○

Model		Speedrower® 160 PLUS	Speedrower® 220 PLUS	Speedrower® 260 PLUS
Precision Farming Solutions				
IntelliView™ IV 10.4-inch color touchscreen display		●	●	●
IntelliCruise™ Automation - Power Cruise Mode		-	●	●
IntelliCruise™ Automation - Eco Cruise Mode		-	●	●
Headland Management with speed control		●	●	●
Electronic disc speed management		-	●	●
Factory IntelliSteer™ auto guidance ready		●	●	●
Factory IntelliSteer™ auto guidance complete level 1 (WAAS)		○	○	○
IntelliSteer™ auto guidance - Field speed range	mph (kph)	0-20 (0-32)	0-20 (0-32)	0-20 (0-32)
IntelliSteer™ auto guidance - Maximum line acquisition angle	degrees	Up to 90°	Up to 90°	Up to 90°
IntelliSteer™ auto guidance - Line acquisition speed range	mph (kph)	0-10 (0-16)	0-10 (0-16)	0-10 (0-16)
IntelliSteer™ auto guidance - High cross track error engagement		●	●	●
Header Drive				
Header drive pump type		Fixed Displacement	Electronic Variable Displacement	Electronic Variable Displacement
Max. header drive pump output at 2,200 engine RPM	gal/min. (L/min.)	31.6 (120)	92 (350)	92 (350)
Max. header drive pump output at 2,600 rpm disc speed	gal/min. (L/min.)	-	78 (296)	78 (296)
Header power reverser		●	●	●
Header flotation		Single Hydraulic (in-cab adjustable)	Independent RH/LH Hydraulic (in-cab adjustable)	Independent RH/LH Hydraulic (in-cab adjustable)
Hydraulic header tilt		●	●	●
Single lever header transport lock system		●	●	●
Header Compatibility				
Haybine® HS14 sickle mower-conditioner heads		●	-	-
Haybine® HS16 sickle mower-conditioner heads		●	●	●
Haybine® HS18 sickle mower-conditioner heads		●	●	●
Durabine™ 416 PLUS disc mower-conditioner heads		-	●	●
Durabine™ 416 PLUS disc mower-specialty heads		-	●	●
Durabine™ 419 PLUS disc mower-conditioner heads		-	-	●
Machine Dimensions				
Length with header	in. (mm)	290.5 (7366) with HS Series	293 (7442) with Durabine PLUS	293 (7442) with Durabine PLUS
Less header and lift arms	in. (mm)	212.3 (5384)	209.2 (5308)	209.2 (5308)
Height	in. (mm)	134.3 (3411)	134.8 (3424)	134.8 (3424)
Wheelbase	in. (mm)	154.1 (3911)	154.1 (3911)	154.1 (3911)
Front tread width	in. (mm)	148.5 (3771)	154.8 (3932)	154.8 (3932)
Rear tread width (adjustable)	in. (mm)	90-105-120 (2286-2667-3048)	90-105-120 (2286-2667-3048)	90-105-120 (2286-2667-3048)
Terraglide™ Rear axle suspension vertical travel	in. (mm)	0-4 (0-101)	0-4 (0-101)	0-4 (0-101)
Terraglide™ Rear axle suspension articulation	degrees	12°	12°	12°
Approximate tractor weight	lbs. (kg)	12,225 (5545)	13,000 (5897)	14,000 (6350)

*Predicted gradeability based on mathematical calculations

**Only available tire options on High-Speed versions

● standard ○ optional - not available