BBI CRICKET AG & TURF



Small Farms / Can be pulled with low HP tractor / Ground Wheel Drive

BBI Cricket Ag & Turf

Conveyor / PTO or Hydraulic Driven Spinners

The BBI Cricket Ag and Turf is a fertilizer and lime spreader designed for precision dry material application. This spreader only requires a 30 to 40 horsepower tractor to pull it. The narrow wheel track width allows it to be maneuvered through narrow paths, while the wide floatation tires are standard to minimize compaction. Wide floatation tires are standard to minimize compaction.

Unique Features

- Can be pulled with a low horsepower tractor (30 40 horsepower)
- External ground wheel driven by traction against the tire
- Ground wheel driven stainless steel mesh chain
- 24 inch dished spinner design for precision coverage
- 15 inch ground clearance
- Flotation tire and turf tire options minimize compaction

BBI Cricket Ag & Turf SpecificationsFertilizer / Lime

I GILIIIZGI / LIIII	
Working Width	Hydraulic - Fertilizer 80 feet, Lime 60 feet
	PTO - Fertilizer 60 feet, Lime 60 feet
Size	8 feet
Capacity (struck)	Standard: 64 cubic feet, struck
	15 inch ground clearance
Hopper Material	Optional: 304 Stainless Steel
	Optional: Painted 409 Stainless Steel
Drive	Standard: Conveyor Ground Wheel Drive
	Standard: Manual Hydraulics to Engage Ground Wheel
	Optional: Conveyor & Spinner Ground Wheel Drive
Conveyor Chain	Standard: 16 inch 304 Stainless Steel Mesh Chain
	Optional: 16 inch Bar Chain in Lieu of Mesh
Press Wheel	Standard: Pneumatic Press Wheel
	Optional: Metal Press Wheel
Spinner Drive	Standard: PTO (540 RPM) driven Spinners (twin 24 inch spinners)
	Standard: PTO (1000 RPM) driven Spinners (twin 24 inch spinners)
	Optional: Hydraulic Spinners (Plug-to-Tractor) w/ ELIMINATOR Manifold
Tires & Suspension	Standard: 12,000 lb rigid single-axle 16.5 x 16.1 10 ply tires. W16C x 16.1 Ag type wheels, 8-Bolt hubs.
PTO Drive Line / CV Joint	Standard: 540 RPM Series 6 CV Joint PTO Shaft
	Standard: 1000 RPM Series 6 CV 1 3/4 20 Spline
	Standard: 1000 RPM Series 6 CV 1 3/8 21 Spline
Hopper Extensions	Standard: None
	Optional: 8 inch Unit Extension Brackets ONLY (without wood)
	Optional: 8 finch Unit 2 inch x 6 inch Extension Brackets with wood
Tarp	Standard: None
	Optional: 8 foot Box Type Tarp w Bow (Vinyl)

BBI CRICKET VINEYARD



BBI Cricket Vinevard Specifications



BBI Cricket Vineyard

inch track

The BBI designed Cricket Vineyard spreader provides an affordable and dependable tool for spreading fertilizer, lime and compost in your vineyard or orchard. This Vineyard or Orchard spreader can clear low overhanging limbs, and the reversible wheels allow a 50 or 60 inch track to accommodate most vineyards.

Unique Features

- Can be pulled with a low horsepower tractor (30 40 horsepower)
- Available in 50 inch and 60 inch outside widths by reversing the wheels
- 2 speed hydraulic conveyor drive
- 24 inch dished spinner design for precision coverage
- Plug to tractor hydraulic driven spinners
- 15 inch ground clearance
- Flotation tires minimize compaction

Fertilizer / Lime / Compost	
Working Width	Fertilizer 80 feet +
	Lime 60 feet
Size	8 feet
Capacity (struck)	Standard: 64 cubic feet, struck
	15 inch ground clearance
Hopper Material	Optional: 304 Stainless Steel
	Optional: Painted 409 Stainless Steel
6 1 1	Optional: Plug to Tractor Hydraulic Manual Controls
	Optional: Plug to Tractor Hydraulic CL 250 Electronic Controls
Controls	Optional: Self Contained Hydraulic Manual Controls
	Optional: Self Contained Hydraulic CL 250 Electronic Controls
Conveyor Chain	Standard: 16 inch Mesh Chain and Heat Shrink Fittings
C-:	Standard: Stainless Steel Spinners and Fins
Spinner and Fins	Optional: Carbon Steel Spinners and Fins
Complete Spinner Shield	Standard: ONE Complete Spinner Shield Assembly
Assembly	Optional: Second Complete Spinner Shield Assembly (if sold separately) NET
Spinner Drive	Standard: Twin 24 inch Diameter Spinners that are Driven by Tractor Supplied Hydraulic
Tires & Suspension	Standard: 7000 lb Rigid Single-Axle with 6 inch on 6 inch AG type Hubs and Spindles available in 50 inch to 60 inch Overall Width. 14L Flotation tires on W11C x 16.1 Reversible Wheels.
Banding Conveyor	Standard: Banding attachment
	Optional: 4 foot Banding Conveyor with Belt
Hitch	Standard: Heavy Duty Clevis Hitch
	Standard: Cast Hitch Option for Pull Type Spreaders - includes Pintle and Clevis Hitch
Wheels	Standard: Reversible 14L Wheels for 50 inch or 60 inch Overall Width
Tarp	Standard: None
	Optional: 8 foot Box Type Tarp w Bow (Vinyl)

BBI SIDESHOOTER



BBI SideShooter SpecificationsDairy Sand / Fish Pellets or Similar Materials

Size	9 feet
Capacity (struck)	192 cubic feet, struck
Hopper Material	Standard: Carbon Steel
Self Contained Hydraulics	Standard: Self Contained Hydraulic System connecting to 540 rpm Tractor PTO
	Standard: Self Contained Hydraulic System connecting to 1000 rpm Tractor PTO
Hopper Conveyor	18 inch wide, 304 Stainless Steel Mesh Chain. Self-Contained Hydraulic System with 35 Gallon Reservoir and PTO Driven Trailer Mounted Heavy-Duty 2 Section Pump.
Conveyor Chain	Standard: 18 inch Stainless Steel Mesh Chain
Discharge Conveyor	Standard: 18 inch Discharge Conveyor
	1 inch Cheated Rubber Transfer Belt - Adjustable to 20 degrees
Frame and Suspension	Standard: 24K Rigid Axle with 10 Bolt Hubs with Heavy-Duty Frame and Hitch
Tires	Standard: 21.5 X 16.1 10 Ply Flotation tires

BBI SideShooter

The SideShooter adds ease to distributing bedding materials in dairy operations through precise, balanced distribution of sand (and/or your bedding material(s) of choice) into all barn styles. SideShooter has also emerged as a must-have piece of equipment for managers of commercial game fisheries and freshwater farms for species such as tilapia and catfish.

Unique Features

- · Side-discharge spreader
- Lightweight and towable
- For use in dairy and fish farms
- Distribution of bedding materials and fish pellets

