

Series 350 Wheel-Type Wing Fold Tandem Disc Harrow

Cutting Width	Bearing Hanger Type	Number of Discs	Approx. Weight	Number of Bearings	Transport Wheels	Wing Size	Approx. DB Hp
Narrow Frame – 22" Round Blades / Base Weight 7 ½" Disc Spacing							
15' 1"	Rigid	48	5,034 lbs.	16	4	5F / 5R	90 HP
15' 1"	Flex	48	5,150 lbs.	16	4	5F / 5R	90 HP
16' 3"	Rigid	52	5,239 lbs.	16	4	6F / 6R	95 HP
16' 3"	Flex	52	5,399 lbs.	16	4	6F / 6R	95 HP
17' 5"	Rigid	56	5,487 lbs.	16	4	7F / 7R	100 HP
17' 5"	Flex	56	5,487 lbs.	16	4	7F / 7R	100 HP
Narrow Frame – 22" Round Blades / Base Weight 9" Disc Spacing							
14' 10"	Rigid	40	4,769 lbs.	16	4	4F / 4R	90 HP
14' 10"	Flex	40	4,929 lbs.	16	4	4F / 4R	90 HP
16' 3"	Rigid	44	5,017 lbs.	16	4	5F / 5R	95 HP
16' 3"	Flex	44	5,177 lbs.	16	4	5F / 5R	95 HP
17' 8"	Rigid	44	5,265 lbs.	16	4	6F / 6R	100 HP
17' 8"	Flex	40	5,425 lbs.	16	4	6F / 6R	100 HP
Narrow Frame – 22" Round Blades / Base Weight 9" FT / 7 ½" RR Disc Spacing							
15' 1"	Rigid	44	4,882 lbs.	16	4	4F / 5R	90 HP
15' 1"	Flex	44	5,042 lbs.	16	4	4F / 5R	90 HP
16' 3"	Rigid	48	5,130 lbs.	16	4	5F / 6R	95 HP
16' 3"	Flex	48	5,290 lbs.	16	4	5F / 6R	95 HP
17' 5"	Rigid	52	5,369 lbs.	16	4	6F / 7R	100 HP
17' 5"	Flex	52	5,529 lbs.	16	4	6F / 7R	100 HP
Wide Frame – 22" Round Blades / Base Weight 7 ½" Disc Spacing							
18' 8"	Rigid	60	6,010 lbs.	24	4	5F / 5R	115 HP
18' 8"	Flex	60	6,250 lbs.	24	4	5F / 5R	115 HP
19' 10"	Rigid	64	6,258 lbs.	24	4	6F / 6R	120 HP
19' 10"	Flex	64	6,498 lbs.	24	4	6F / 6R	120 HP
21' 0"	Rigid	68	6,506 lbs.	24	4	7F / 7R	125 HP
21' 0"	Flex	68	5,746 lbs.	24	4	7F / 7R	125 HP
Wide Frame – 22" Round Blades / Base Weight 9" Disc Spacing							
19' 1"	Rigid	52	5,812 lbs.	24	4	4F / 4R	115 HP
19' 1"	Flex	52	6,052 lbs.	24	4	4F / 4R	115 HP
20' 6"	Rigid	56	6,037 lbs.	24	4	5F / 5R	120 HP
20' 6"	Flex	56	6,277 lbs.	24	4	6F / 6R	120 HP
21' 11"	Rigid	60	6,285 lbs.	24	4	6F / 6R	125 HP
21' 11"	Flex	60	6,525 lbs.	24	4	6F / 6R	125 HP
Wide Frame – 22" Round Blades / Base Weight 9" FT / 7 ½" RR Disc Spacing							
18' 8"	Rigid	56	5,902 lbs.	24	4	4F / 5R	115 HP
18' 8"	Flex	56	6,142 lbs.	24	4	4F / 5R	115 HP
19' 10"	Rigid	60	6,150 lbs.	24	4	5F / 6R	120 HP
19' 10"	Flex	60	6,395 lbs.	24	4	5F / 6R	120 HP
21' 0"	Rigid	64	6,403 lbs.	24	4	6F / 7R	125 HP
21' 0"	Flex	64	6,643 lbs.	24	4	6F / 7R	125 HP