

Series 351 Wheel-Type Tandem Disc Harrow

Cutting Width	Bearing Hanger Type	Number of Discs	Approx. Weight	Number of Bearings	Transport Wheels	Approx. DB Hp
Narrow Frame – 20" Round Blades / Base Weight 7 ½" Disc Spacing						
9' 3"	Rigid	28	3,932 lbs.	8	4	55 HP
9' 3"	Flex	28	4,029 lbs.	8	4	55 HP
10' 5"	Rigid	32	4,144 lbs.	8	4	60 HP
10' 5"	Flex	32	4,289 lbs.	8	4	60 HP
11' 6"	Rigid	36	4,356 lbs.	16	4	65 HP
11' 6"	Flex	36	4,550 lbs.	16	4	65 HP
Narrow Frame – 20" Round Blades / Base Weight 9" Disc Spacing						
9' 4"	Rigid	24	3,842 lbs.	8	4	55 HP
9' 4"	Flex	24	3,940 lbs.	8	4	55 HP
10' 9"	Rigid	28	4,096 lbs.	8	4	60 HP
10' 9"	Flex	28	4,192 lbs.	8	4	60 HP
12' 2"	Rigid	32	4,350 lbs.	12	4	65 HP
12' 2"	Flex	32	4,495 lbs.	12	4	65 HP
Narrow Frame – 20" Round Blades / Base Weight 9" FT / 7 ½" RR Disc Spacing						
9' 3"	Rigid	26	3,890 lbs.	8	4	55 HP
9' 3"	Flex	26	3,987 lbs.	8	4	55 HP
10' 5"	Rigid	30	4,120 lbs.	8	4	60 HP
10' 5"	Flex	30	4,217 lbs.	8	4	60 HP
11' 6"	Rigid	34	4,356 lbs.	12	4	65 HP
11' 6"	Flex	34	4,525 lbs.	12	4	65 HP
Wide Frame – 20" Round Blades / Base Weight 7 ½" Disc Spacing						
12' 10"	Rigid	40	4,858 lbs.	16	4	70 HP
12' 10"	Flex	40	5,052 lbs.	16	4	70 HP
14' 0"	Rigid	44	5,112 lbs.	16	4	75 HP
14' 0"	Flex	44	5,306 lbs.	16	4	75 HP
15' 2"	Rigid	48	5,306 lbs.	16	4	80 HP
15' 2"	Flex	48	5,560 lbs.	16	4	80 HP
16' 4"	Rigid	52	5,620 lbs.	16	4	85 HP
16' 4"	Flex	52	5,814 lbs.	16	4	85 HP
Wide Frame – 20" Round Blades / Base Weight 9" Disc Spacing						
13' 7"	Rigid	36	4,737 lbs.	16	4	70 HP
13' 7"	Flex	36	4,931 lbs.	16	4	70 HP
14' 10"	Rigid	40	4,997 lbs.	16	4	75 HP
14' 10"	Flex	40	5,191 lbs.	16	4	75 HP
16' 3"	Rigid	44	5,245 lbs.	16	4	80 HP
16' 3"	Flex	44	5,439 lbs.	16	4	80 HP
Wide Frame – 20" Round Blades / Base Weight 9" FT / 7 ½" RR Disc Spacing						
14' 0"	Rigid	40	4,925 lbs.	16	4	75 HP
14' 0"	Flex	40	5,118 lbs.	16	4	75 HP
15' 2"	Rigid	44	5,185 lbs.	16	4	80 HP
15' 2"	Flex	44	5,378 lbs.	16	4	80 HP
16' 4"	Rigid	48	5,433 lbs.	16	4	85 HP
16' 4"	Flex	48	5,627 lbs.	16	4	85 HP