

TORNADO BRC



Standard duty rotary cutters 20-60 HP (15-45 KW) 540 rpm - Cat. 1

- Cutting heights: from 1" to 9 1/4"
- 10 gauge reinforced deck
- Heavy duty shielded PTO shaft with shear bolt or slip clutch safety (1 3/8" ASAE cat. 4)
- Oval stump jumper standard on 48", 60" & 72" sizes
- Spring steel blades
- 1" cutting capacity
- Front & rear safety shields standard
- Laminated tail wheel (4"x8"x15")
- 3 Point linkage, cat. 1
- Floating top link
- Fully welded round back frame



TECHNICAL FEATURES

STANDARD FEATURES

OPTIONAL EQUIPMENT

MANUALS

MODELS WITH SHEAR BOLT

Model	HP	Working width	Overall width	Weight lbs	Ship lbs	Rotor rpm	Blades tip speed (ft/min)	# Blades & sizes	Cutting height	Laminated wheel size	Driveline 1 3/8"
BRC-142	20-60	42"	47"	383	397	1,042	11,437	(2) 3/8"x2 3/4"	1" to 9 1/4"	4"x8"x15"	ASAE cat. 4 shear bolt
BRC-148	25-60	48"	56"	443	457	1,042	12,560	(2) 3/8"x2 3/4"	1" to 9 1/4"	4"x8"x15"	ASAE cat. 4 shear bolt
BRC-160	30-60	60"	68"	528	591	794	11,948	(2) 1/2"x3"	1" to 9 1/4"	4"x8"x15"	ASAE cat. 4 shear bolt
BRC-172	35-60	72"	79"	601	675	794	14,232	(2) 1/2"x3"	1" to 9 1/4"	4"x8"x15"	ASAE cat. 4 shear bolt

MODELS WITH SLIP CLUTCH

Model	HP	Working width	Overall width	Weight lbs	Ship lbs	Rotor rpm	Blades tip speed (ft/min)	# Blades & sizes	Cutting height	Laminated wheel size	Driveline 1 3/8"
BRC-242	20-60	42"	47"	401	415	1,042	11,437	(2) 3/8"x2 3/4"	1" to 9 1/4"	4"x8"x15"	ASAE cat. 4 slip clutch
BRC-248	25-60	48"	56"	461	475	1,042	12,560	(2) 3/8"x2 3/4"	1" to 9 1/4"	4"x8"x15"	ASAE cat. 4 slip clutch
BRC-260	30-60	60"	68"	539	613	794	11,948	(2) 1/2"x3"	1" to 9 1/4"	4"x8"x15"	ASAE cat. 4 slip clutch
BRC-272	35-60	72"	79"	612	686	794	14,232	(2) 1/2"x3"	1" to 9 1/4"	4"x8"x15"	ASAE cat. 4 slip clutch

WARNING: Because of possible injury from thrown objects, all rotary cutters are potentially dangerous.

Any rotary cutter intended for use along roadways or other locations where people may be present must be used with safety shielding in place.

WARNING: When using a quick hitch on a PTO driven implement, always ensure there is proper overlap prior to use. If there is not the minimum 6" overlap, do not use. Contact your dealer to purchase a longer driveline.

TORNADO RMD



Medium duty rotary cutters
35-80 HP (26-60 KW)
540 rpm - Cat. 1

- Cutting heights: from 1" to 9 1/4"
- Replaceable skids
- Highly engineered & rugged gearbox
- Heavy duty shielded PTO shaft with slip clutch safety (1 3/8" ASAE cat. 4)
- 3 point linkage, cat. 1
- Floating top link
- Exceptionally heavy duty 1/2"x4" spring steel blades
- 2" cutting capacity
- High blade tip speed
- Laminated tail wheel with tapered roller bearings (4"x8"x15")
- Oval heavy duty stump jumper standard
- Heavy duty reinforced 8 gauge deck
- Front & rear protective chain shields standard



TECHNICAL FEATURES

STANDARD FEATURES

MANUALS

Model	HP	Working width	Overall width	Weight lbs	Ship lbs	Rotor rpm	Blades tip speed (ft/min)	# Blades & sizes	Cutting height	Laminated wheel size	Driveline 1 3/8"
RMD-360	35-80	60"	68"	695	695	855	13,189	(2) 1/2"x4"	1" to 9 1/4"	4"x8"x15"	ASAE cat. 4 slip clutch
RMD-372	40-80	72"	80"	785	785	855	15,748	(2) 1/2"x4"	1" to 9 1/4"	4"x8"x15"	ASAE cat. 4 slip clutch

WARNING: Because of possible injury from thrown objects, all rotary cutters are potentially dangerous. Any rotary cutter intended for use along roadways or other locations where people may be present must be used with safety shielding in place.

WARNING: When using a quick hitch on a PTO driven implement, always ensure there is proper overlap prior to use. If there is not the minimum 6" overlap, do not use. Contact your dealer to purchase a longer driveline.

TORNADO RHD



Heavy duty rotary cutters 50-100 HP (37-74 KW) 540 rpm - Cat. 1 & 2

- Cutting heights: from 2" to 8"
- Replaceable skids
- Highly engineered & rugged gearbox
- Heavy duty shielded PTO shaft with slip clutch safety (1 3/8" ASAE cat. 6)
- 3 point linkage, cat. 1 & 2
- Floating top link
- Front & rear protective chain shields standard
- Exceptionally heavy duty 1/2"x4" spring steel blades
- 3" cutting capacity
- High blade tip speed
- Laminated tail wheel with tapered roller bearings (5"x8"x15")
- Oval heavy duty stump jumper standard
- Heavy duty reinforced deck



TECHNICAL FEATURES

STANDARD FEATURES

MANUALS

Model	HP	Working width	Overall width	Weight lbs	Ship lbs	Rotor rpm	Blades tip speed (ft/min)	# Blades & sizes	Cutting height	Laminated wheel size	Driveline 1 3/8"
RHD-472	50-100	72"	76"	1,025	1,025	748	13,878	(2) 1/2"x4"	2" to 8"	5"x8"x15"	ASAE cat. 6 slip clutch
RHD-484	60-100	84"	88"	1,200	1,200	748	16,191	(2) 1/2"x4"	2" to 8"	5"x8"x15"	ASAE cat. 6 slip clutch

WARNING: Because of possible injury from thrown objects, all rotary cutters are potentially dangerous.

Any rotary cutter intended for use along roadways or other locations where people may be present must be used with safety shielding in place.

WARNING: When using a quick hitch on a PTO driven implement, always ensure there is proper overlap prior to use. If there is not the minimum 6" overlap, do not use. Contact your dealer to purchase a longer driveline.