

Coneqtec Universal Cold Planer Specifications

AP Series							
	AP 300	AP 400	AP 450	AP 600	AP 760	AP 800	AP 1000
Cutting width	12"	16"	18"	24"	30"	32"	40"
Cutting depth	6"	6"	6"	6"	6"	6"	6"
Tilt capability (right or left)	15°	15°	15°	15°	7.5°	7.5°	7.5°
Slide shift travel	24"	24"	24"	24"	24"	24"	24"
Shipping weight (lbs)	1500	1600	1700	1900	2200	2450	2700
Hydraulic HP Range	24-70	32-100	36-100	48-100	60-100	62-100	70-100
Flow type	Hi/Std	Hi/Std	Hi	Hi	Hi	Hi	Hi
# Teeth	38	48	56	68	78	88	108

APX Series				
	APX 300	APX 400	APX 450	APX 600
Cutting width	12"	16"	18"	24"
Cutting depth	6"	6"	6"	6"
Tilt capability (right or left)	15°	15°	15°	15°
Slide shift travel	24"	24"	24"	24"
Shipping weight (lbs)	1200	1500	1600	1700
Hydraulic HP Range	24-80	32-80	36-80	48-80
Flow type	Hi/Std	Hi/Std	Hi	Hi
# Teeth	38	48	56	68