LASSIE

INDUSTRIAL

MODELS:

2760KW 27hp, 60" Deck 3560KW 35hp, 60" Deck 4060VGE 40hp, 60" Deck **3572KW** 35hp, 72" Deck 4072VGE 40hp, 72" Deck





A TRUE CLASSIC AMERICAN WORKHORSE.

The **Classic** is the perfect definition of a workhorse mower with the combination of commercial quality and industrial features.

- Power and More Power Powered by Kawasaki* FX or Vanguard® Big Block EFI engines up to 40 horsepower to power through the tough jobs with ease.
- Lifetime Warranty Frame The strongest frame in the industry with a 1"x 2" 7 gauge steel construction guaranteed not to break.
- T-Gear Box Eliminates side-load on pumps and backed with a 5-year/3,000 hour warranty.
- Complete Discharge Control An operator controlled discharge chute (OCDC) allows you to switch from normal discharge to closing the chute on the fly.
- Tried and True Decks Offered in two productive deck widths (60" and 72") the Elite X Deck has been the staple piece to Dixie Chopper's reputation of cleanly cutting all types of grass.
- Comfort Ride Our suspension seat comes standard on every Classic model to provide a smooth ride in the roughest terrain.



Suspension Seat - Full suspension for ultimate comfort all day long



Pumps & Wheel Motors - Stronger transmissions for extended system life



60" and 72" Elite X Deck - Gives a quality cut in all types of grass



Turbinator* Pre-Cleaner - Exclusive feature removes debris for cleaner air



Spindle Package - Maintenance-free spindles and cooling fans come standard



*Unlimited hour limited warranty, see dealer for complete warranty details



	60" Deck		72" Deck		
Model	2760KW	3560KW	4060VGE	3572KW	4072VGE
Engine					
Manufacturer	Kawas	Kawasaki* FX		Kawasaki* FX	Vanguard® EFI
Horsepower	27	35	40	35	40
Displacement	852cc	999cc	993cc	999сс	993cc
Air-cleaner	4 stage & Turbinator® Pre-Cleaner				
Cooling	Air-cooled Air-cooled				
Starter	Electric				
Engine warranty	3-Year				

Drive System			
Pumps	Hydro-Gear* 16cc		
Wheel motors	Parker® DG280		
Ground speed	12 mph		
Parking brake	Automotive Style		
Towing capacity	2,000 lbs		

Mower Deck			
Deck size	60"	72"	
Acres/hour*	5.8	7	
Cutting height	1.25" - 5"		
OCDC (operator controlled discharge chute)	Standard		
Deck height adjustments	Manual lift, 1/4" increments		
Electric lift	Optional		
Deck engagement	Ogura® 250 ft-lbs		
Construction	10 ga formed & welded	7 ga formed & welded	
Top plate	7 ga bolted (not welded)		
Blades	3 - 20.5" × 2.5" 3 - 24" × 2.5"		
Blade tip speed (approximate)	18,000 fpm		
Spindles	1.25" effective diameter machined shaft		
Spindle housings	Peer® Turf Xtreme™ ductile iron (sealed)		
Spindle cooling fans	Standard (3)		
Anti-scalp rollers	4	5	
Pulleys	Vented split 3/16" steel deep groove		

General				
Battery	12 Volt, 350cca			
Digital display	Tachometer, hour meter, voltmeter, service alerts			
Fuel capacity	8 gallons	10 gallons	12 gallons	
Rear tires	25 x 12-12 GrassMaster			
Front tires	15 x 6-8 (run-flat)			
Frame	Welded 1" x 2" tube, 7 ga formed			
Floor-pan	Removable, steel			
Seat	Full suspension, adjustable seat w/ armrests			
Springer Forks	Optional			

Dimensions				
Overall height	53"			
Overall height (rollbar up)	78"			
Overall width	65.5"		76"	
Overall length	78.5" 78"		80"	
Overall length (rollbar down)	81"		83"	
Weight	1134 lbs	1228 lbs	1425 lbs	

